Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

- 1-18. (cancelled)
- 19. (currently amended) A medical device, comprising:
- a proximal shaft section and a distal shaft section extending distally of the proximal shaft section;

the proximal shaft section includes a tubular shaft having a proximal end and a distal end; a plurality of slits defined in the tubular shaft;

wherein a greater number of slits are disposed near the distal end of the tubular shaft than near the proximal end of the tubular shaft;

the distal shaft section including a braid attached to the distal end of the tubular shaft and at least a distal portion of the braid is disposed over and contacting a polymer layer;

wherein the braid is disposed over the distal end of the tubular shaft such that a portion of the braid is located proximal of the distal end of the tubular shaft; and

- a polymer layer disposed over the tubular shaft and the braid.
- (previously presented) The medical device of claim 19, wherein the distal shaft section is deflectable.
- 21. (previously presented) The medical device of claim 19, wherein the tubular shaft has a longitudinal axis and wherein the slits are arranged generally perpendicular to the longitudinal axis.
- 22. (previously presented) The medical device of claim 19, wherein the medical device has a transition in stiffness from the proximal shaft section to the distal shaft section.

Appl. No. 10/804,360 Amdt. dated September 21, 2009 Reply to Final Office Action of May 22, 2009

23. (Cancelled)

24. (previously presented) The medical device of claim 19, wherein the number of slits per unit length is greater near the distal end of the tubular shaft than near the proximal end of the tubular shaft.

25. (previously presented) The medical device of claim 19, wherein the slits have a first depth near the proximal end of the tubular shaft and a second depth near the distal end of the tubular shaft, and wherein the second depth is deeper than the first depth.

26. (previously presented) The medical device of claim 19, wherein the tubular shaft is a nickel-titanium alloy tube.

27. (cancelled)

28. (currently amended) A medical device, comprising:

a proximal shaft portion and a distal shaft portion;

the proximal shaft portion including a tubular member having a proximal end and a distal end, the tubular member including a plurality of slits defined in the tubular member;

the distal shaft portion including a braid, the braid attached to the tubular member and extending distally therefrom;

wherein the braid is disposed over the distal end of the tubular member such that a portion of the braid is located proximal of the distal end of the tubular member; and

a polymer layer disposed over the tubular member and the braid and extending distally to a distal end of the distal shaft portion.

 (previously presented) The medical device of claim 28, wherein the distal shaft portion is deflectable. Appl. No. 10/804,360 Amdt. dated September 21, 2009 Reply to Final Office Action of May 22, 2009

30. (previously presented) The medical device of claim 28, wherein the tubular member has a longitudinal axis and wherein the slits are arranged generally perpendicular to the longitudinal axis.

31. (previously presented) The medical device of claim 28, wherein the medical device has a transition in stiffness from the proximal shaft portion to the distal shaft portion.

32. (previously presented) The medical device of claim 28, wherein a greater number of slits are disposed near the distal end of the tubular member than near the proximal end of the tubular member.

33. (previously presented) The medical device of claim 28, wherein the number of slits per unit length is greater near the distal end of the tubular member than near the proximal end of the tubular member.

34. (previously presented) The medical device of claim 28, wherein the slits have a first depth near the proximal end of the tubular member and a second depth near the distal end of the tubular member, and wherein the second depth is deeper than the first depth.

35. (previously presented) The medical device of claim 28, wherein the tubular member is a nickel-titanium alloy tube.

36. (cancelled)

37. (currently amended) A medical device, comprising:

a slotted tubular member having a plurality of slots therein, the slotted tubular member having a proximal end, a distal end, and a longitudinal axis;

wherein the slots vary in number, location, frequency, size, or depth so that the tubular member varies in stiffness between the proximal end and the distal end;

a braid attached to the distal end of the tubular member and extending distally therefrom;

Appl. No. 10/804,360 Amdt. dated September 21, 2009 Reply to Final Office Action of May 22, 2009

wherein the braid is disposed over the distal end of the tubular member such that a portion of the braid is located proximal of the distal end of the tubular member shaft <u>and at least</u> a <u>distal portion of the braid is disposed over and contacting a polymer layer;</u> and

a polymer layer disposed over the tubular member and the braid <u>and extending distally to a distal end of the distal shaft portion</u> so as to define a catheter shaft.

38. (previously presented) The medical device of claim 37, wherein the slots defined are arranged generally perpendicular to the longitudinal axis.

39-41. (cancelled)